



# EpiMax 900WB

## Water Based Clear PU Sealer

### Description

EpiMax 900WB Water Based Clear PU Sealer is a durable, stain resistant, non-yellowing, cross linking protective sealer with excellent adhesion and colour and gloss retention when applied to polished concrete surfaces primed with two pack epoxies.

This system can also be used as a clear top coat for two pack coloured epoxy systems.

EpiMax 900WB enhances the appearance, stain resistance, and clean-ability of epoxy based coatings generally.

Fully cured, it offers good resistance to general chemicals and solvents.

This system is an excellent companion product to the EpiMax 333WB XP range for performance concrete protection.

### Advantages

- Single pack
- Infinite work time
- Fast application by roller or spray
- Meets GBCA Low VOC standard
- No odour impact during application phase
- Excellent adhesion to clean surfaces
- Low colour
- Externally durable

### Typical applications

- Commercial centres
- Residential
- Industrial facilities

### Typical properties

- Set to touch time: 4 - 6 hours approx. (25 deg C)
- Recoat window: 12 - 24 hours
- Full cure: 5 days

### Chemical resistance

- Acids: Good
- Alkalies: Good
- Water: Excellent
- Alcohols: Excellent
- Hydrocarbons: Excellent

### Stain resistance

Good resistance to most stains, oils, grease and tyre-marks



---

### **Estimating data**

10 - 12 sq.m/ltr approx. unsealed surfaces

12 - 15 sq.m/ltr approx. sealed surfaces

Apply in 2-3 coats.

### **Sub-floor preparation**

Concrete should be at least 28 days old. Ensure sub-floor is clean, dry and free of additives, curing agents, oils, etc. Prepare sub-floor by professional grinding or captive blast cleaning as applicable to expose firmly adhered aggregate. Allow to dry if wet.

Always confirm preparation adequacy.

If sealing freshly applied epoxy coatings, apply within specified re-coat window.

If sealing existing epoxy coatings, scrub or lightly grind first and confirm adhesion in a test area.

Apply with a short nap roller or airless spray.

### **Packaging**

EpiMax 900WB is available in 20 litre packs.

Ordering Information: 20 litre 9090920

### **Safety precautions**

Read **Material Safety Data Sheet** before commencing any application. Keep away from children. Avoid contact with skin and avoid breathing vapour. Always provide adequate personal protection (gloves & goggles etc) during use. Always provide adequate ventilation, especially in confined spaces. If poisoning occurs, call Doctor or Poisons Information Centre.

Phone 13 11 26. If swallowed, DO NOT induce vomiting. Give plenty of water or milk. If skin contact occurs, quickly remove contaminated clothing and wash affected areas thoroughly with soap and water.

