



# EpiMax SAFETY DATA SHEET

Product Name **EPIMAX 999UVX GLOSS BASE**

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

<b>Supplier Name</b>	EPIMAX TECHNOLOGIES PTY LTD
<b>Address</b>	4/3 Moorebank Avenue, Moorebank, NSW, AUSTRALIA, 2170
<b>Telephone</b>	1300 721 522
<b>Fax</b>	(02) 9904 3207
<b>Emergency</b>	1300 721 522
<b>Synonym(s)</b>	999UVX GLOSS BASE • 40999970 - PRODUCT CODE • MODIFIED EPOXY RESINS
<b>Use(s)</b>	BASE • TWO COMPONENT EPOXY SYSTEM
<b>SDS Date</b>	09/08/18

## 2. HAZARDS IDENTIFICATION

<b>GHS Classifications</b>	Skin corrosion / irritation: Category 2 Skin sensitization: Category 1 Aquatic Chronic: Category 3
----------------------------	--



### HAZARD STATEMENTS

H315	Causes skin irritation
H317	May cause an allergic skin reaction
H412	Harmful to aquatic life with long lasting effects
H319	Causes serious eye irritation

### PREVENTION AND RESPONSE STATEMENTS

P262	Do not get in eyes, on skin, or on clothing
P264	Wash hands thoroughly after handling
P272	Contaminated clothing should not be allowed of workplace
P273	Avoid release to the environment
P280	Wear protective gloves and eye protection
P302+352	IF ON SKIN, wash with plenty of soap and water
P362	Take off contaminated clothing and wash before use
P333+313	If skin irritation or rash occurs, get medical advice / attention
P305+351	IF IN EYES, rinse cautiously with water for several minutes
P337+13	If eye irritation persists, get medical advice / attention
P391	Collect spillage
501	Dispose of contents / containers in accordance with local regulation

Product Name: **EPIMAX 999UVX GLOSS BASE**

<b>UN No.</b>	None Allocated	<b>DG CLASS</b>	None Allocated	<b>Subsidiary Risk(s)</b>	None Allocated
<b>Packing Group</b>	None Allocated	<b>Hazchem Code</b>	None Allocated		

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

<b>Ingredient</b>	<b>CAS NO.</b>	<b>HAZARD</b>	<b>Content</b>
EPOXY RESIN	25068-38-6	Xi, N	15% - 20%
PROYLENE GLYCOL PHENOL ETHER	9036-19-5	N	<2.5%
NON HAZARDOUS INGREDIENTS			TO 100%

### 4. FIRST AID MEASURES

<b>Eye</b>	If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.
<b>Inhalation</b>	If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or an Airline respirator (in poorly ventilated areas). Apply artificial respiration if not breathing.
<b>Skin</b>	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.
<b>Ingestion</b>	For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.
<b>Special Treatment</b>	Treat symptomatically.

### 5. FIRE FIGHTING MEASURES

<b>Special Hazards</b>	May evolve toxic gases (carbon oxides, phenols, hydrocarbons) when heated to decomposition.
<b>Advice for firefighters</b>	Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.
<b>Extinguishing Media</b>	Dry agent, carbon dioxide or foam. Prevent contamination of drains or waterways.
<b>Hazchem Code</b>	None Allocated

### 6. ACCIDENTAL RELEASE MEASURES

<b>Spillage</b>	Contact emergency services where appropriate. Use personal protective equipment. Clear area of all unprotected personnel. Ventilate area where possible. Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal. Eliminate all ignition sources.
-----------------	--

Product Name: **EPIMAX 999UVX GLOSS BASE**

## 7. STORAGE AND HANDLING

**Storage** Store tightly sealed in a cool, dry, well ventilated area, removed from oxidising agents, acids, alkalis, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Large storage areas should be banded and have appropriate fire protection and ventilation systems. Store as a Class C1 Combustible Liquid (AS1940).

**Precautions for safe handling** Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTIONS

**Exposure Stds** No exposure standards allocated.

**Biological Limits** No biological limit allocated.

**Engineering Controls** Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended.

**PPE** Wear splash-proof goggles, nitrile or viton (R) gloves, coveralls and a Type A (Organic vapour) respirator. If sanding dry product, wear: a Class P1 (Particulate) respirator. If spraying, with prolonged use, or if in confined areas, wear: impervious coveralls and an Air-line respirator.



## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	CLEAR LIQUID	<b>Solubility (water)</b>	SOLUBLE
<b>Odour</b>	AMINE LIKE	<b>Specific Gravity</b>	1.1 – 2.0
<b>pH</b>	6.5-7.5	<b>% Volatiles</b>	<2%
<b>Vapour Pressure</b>	NOT AVAILABLE	<b>Flammability</b>	NON COMBUSTIBLE
<b>Vapour Density</b>	NOT AVAILABLE	<b>Flash Point</b>	NOT AVAILABLE
<b>Boiling Point</b>	100°C	<b>Upper Explosion Limit</b>	NOT AVAILABLE
<b>Melting Point</b>	NOT AVAILABLE	<b>Lower Explosion Limit</b>	NOT AVAILABLE
<b>Evaporation Rate</b>	NOT AVAILABLE		
<b>Autoignition Rate</b>	NOT AVAILABLE	<b>Decomposition Temperature</b>	NOT AVAILABLE
<b>Partition Coefficient</b>	NOT AVAILABLE	<b>Viscosity</b>	NOT AVAILABLE

## 10. STABILITY AND REACTIVITY

**Chemical Stability** Stable under recommended conditions of storage.

**Conditions to avoid** Avoid heat, sparks, open flames and other ignition sources.

**Material to avoid** Incompatible with oxidising agents (eg. hypochlorites), acids (eg. nitric acid), alkalis (eg. hydroxides), heat and ignition sources.

**Product Name: EPIMAX 999UVX GLOSS BASE**

**Hazardous Decomposition Products** May evolve toxic gases (carbon oxides, phenols, hydrocarbons) when heated to decomposition.  
**Hazardous Reactions** Hazardous polymerization is not expected to occur.

**11. TOXICOLOGICAL INFORMATION**

**Health hazard summary** Irritant - low to moderate toxicity. This product has the potential to cause adverse health effects with over exposure. Use safe work practices to avoid eye or skin contact and inhalation. May cause sensitisation by skin contact. The cured product is considered nontoxic.

**Eye** Irritant. Contact may result in irritation, lacrimation, pain and redness.

**Inhalation** Irritant. Over exposure whilst curing may result in irritation of the nose and throat, coughing, possible sensitisation with asthma-like symptoms and pulmonary oedema at high levels.

**Skin** Irritant. Contact may result in irritation, redness, rash and dermatitis. May cause sensitisation by skin contact.

**Ingestion** Low to moderate toxicity. Ingestion may result in gastrointestinal irritation, nausea, vomiting, abdominal pain and diarrhoea.

**Toxicity Data** **Short Term Hazards (Acute Exposure):**  
**LD50 values that is relevant for classification:**  
CAS 25068-38-6 Reaction product Bisphenol-A-Epoxy Resin  
Oral LD50 > 5000mg/kg (rat)  
Dermal LD50 > not determined

**Long Term Hazards**  
Inhaled: prolonged exposure to high concentrations of vapour may affect the central nervous  
On the skin: Product may be a skin sensitiser in some individuals  
On the eye: Corneal Injury

**12. ECOLOGICAL INFORMATION**

**Other adverse effects** Limited ecotoxicity data was available for this product at the time this report was prepared. Ensure appropriate measures are taken to prevent this product from entering the environment.

**13. DISPOSAL CONSIDERATIONS**

**Waste disposal** Mix parts A + B together (small amounts), absorb with sand, vermiculite or similar and dispose of to an approved landfill site. Ensure protective equipment is worn when mixing. Do not seal containers/tins until reaction is complete. Contact the manufacturer for additional information. Prevent contamination of drains or waterways as environmental damage may result.

**Legislation** Dispose of in accordance with relevant local legislation.

**14. TRANSPORT INFORMATION**

Product Name: **EPIMAX 999UVX GLOSS BASE**

**NOT CLASSIFIED AS A DANGEROUS GOOD THE CRITERIA OF THE ADG CODE**

Shipping Name	NONE ALLOCATED				
UN No.	NONE ALLOCATED	DG CLASS	NONE ALLOCATED	Subsidiary Risk(s)	NONE ALLOCATED
Packing Group	NONE ALLOCATED	Hazchem Code	NONE ALLOCATED	GTEPG	NONE ALLOCATED

**15. REGULATORY INFORMATION**

**Poison Schedule** A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).

**AICS** All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

**16. OTHER INFORMATION**

**Additional information** This product is used in conjunction with Epimax 999UVX GLOSS ACTIVATOR.

**WELDING - SANDING - CUTTING DRIED OR CURED PRODUCT:** If sanding, cutting or welding dried or cured product, adverse health effects may be avoided by the use of appropriate engineering controls and/or personal protective equipment. If welding, wear a Class P2 (Metal fume) respirator and depending on the nature of the surface being welded, additional protection (eg. for organic vapours/acid gas) may also be required. A Class P1 (Particulate) respirator is recommended if dust is generated.

**EPOXY - PHENOXY RESINS AND POLYURETHANES:** Where spray painting with two or more component epoxy resins or polyurethane paints is undertaken, an employee shall wear a air-line respirator, full length chemically resistant coveralls and gloves. Further, if an individual is to enter an enclosed booth where a vapour or gas curing process is occurring, an air-line respirator is required. Once cured, these resins are considered nontoxic.

**RESPIRATORS:** In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken.

Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

**ABBREVIATIONS:**

ACGIH - American Conference of Industrial Hygienists.

ADG - Australian Dangerous Goods.

BEI - Biological Exposure Indice(s).

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.

CNS - Central Nervous System.

EC No - European Community Number.

HSNO - Hazardous Substances and New Organisms.

IARC - International Agency for Research on Cancer.

mg/m<sup>3</sup> - Milligrams per Cubic Metre.

NOS - Not Otherwise Specified.

pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).

ppm - Parts Per Million.

RTECS - Registry of Toxic Effects of Chemical Substances.

**Product Name:**

**EPIMAX 999UVX GLOSS BASE**

STEL - Short Term Exposure Limit.

SWA - Safe Work Australia.

TWA - Time Weighted Average.



# EpiMax SAFETY DATA SHEET

Product Name **EPIMAX 999UVX GLOSS ACTIVATOR**

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

<b>Supplier Name</b>	EPIMAX TECHNOLOGIES PTY LTD
<b>Address</b>	4/3 Moorebank Avenue, Moorebank, NSW, AUSTRALIA, 2170
<b>Telephone</b>	1300 721 522
<b>Fax</b>	(02) 9904 3207
<b>Emergency</b>	1300 721 522
<b>Synonym(s)</b>	999UVX GLOSS ACTIVATOR • 40999960 - PRODUCT CODE • MODIFIED EPOXY RESINS
<b>Use(s)</b>	ACTIVATOR • TWO COMPONENT EPOXY SYSTEM
<b>SDS Date</b>	09/08/18

## 2. HAZARDS IDENTIFICATION

<b>GHS Classifications</b>	Skin corrosion / irritation: Category 2 Skin sensitization: Category 1 Aquatic Chronic: Category 3
----------------------------	--



### HAZARD STATEMENTS

H315	Causes skin irritation
H317	May cause an allergic skin reaction
H412	Harmful to aquatic life with long lasting effects
H319	Causes serious eye irritation

### PREVENTION AND RESPONSE STATEMENTS

P262	Do not get in eyes, on skin, or on clothing
P264	Wash hands thoroughly after handling
P272	Contaminated clothing should not be allowed of workplace
P273	Avoid release to the environment
P280	Wear protective gloves and eye protection
P302+352	IF ON SKIN, wash with plenty of soap and water
P362	Take off contaminated clothing and wash before use
P333+313	If skin irritation or rash occurs, get medical advice / attention
P305+351	IF IN EYES, rinse cautiously with water for several minutes
P337+13	If eye irritation persists, get medical advice / attention
P391	Collect spillage
501	Dispose of contents / containers in accordance with local regulation

Product Name:

**EPIMAX 999UVX GLOSS ACTIVATOR**

<b>UN No.</b>	None Allocated	<b>DG CLASS</b>	None Allocated	<b>Subsidiary Risk(s)</b>	None Allocated
<b>Packing Group</b>	None Allocated	<b>Hazchem Code</b>	None Allocated		

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

<b>Ingredient</b>	<b>Formula</b>	<b>CAS NO.</b>	<b>Content</b>
M-PHENYLENBIS (METHYLAMINE)	NOT AVAILABLE	001477-55-0	<2.5%
TRIETHYLENETETRAMINE	NOT AVAILABLE	000112-24-3	<2.5%
NON HAZARDOUS INGREDIENTS			TO 100%

**4. FIRST AID MEASURES**

<b>Eye</b>	If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.
<b>Inhalation</b>	If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or an Airline respirator (in poorly ventilated areas). Apply artificial respiration if not breathing.
<b>Skin</b>	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.
<b>Ingestion</b>	For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.
<b>Special Treatment</b>	Treat symptomatically.

**5. FIRE FIGHTING MEASURES**

<b>Special Hazards</b>	May evolve toxic gases (carbon oxides, phenols, hydrocarbons) when heated to decomposition.
<b>Advice for firefighters</b>	Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.
<b>Extinguishing Media</b>	Dry agent, carbon dioxide or foam. Prevent contamination of drains or waterways.
<b>Hazchem Code</b>	None Allocated

**6. ACCIDENTAL RELEASE MEASURES**

<b>Spillage</b>	Contact emergency services where appropriate. Use personal protective equipment. Clear area of all unprotected personnel. Ventilate area where possible. Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal. Eliminate all ignition sources.
-----------------	--



Product Name:

## EPIMAX 999UVX GLOSS ACTIVATOR

### 7. STORAGE AND HANDLING

<b>Storage</b>	Store tightly sealed in a cool, dry, well ventilated area, removed from oxidising agents, acids, alkalis, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Large storage areas should be banded and have appropriate fire protection and ventilation systems. Store as a Class C1 Combustible Liquid (AS1940).
<b>Precautions for safe handling</b>	Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTIONS

<b>Exposure Stds</b>	No exposure standards allocated.
<b>Biological Limits</b>	No biological limit allocated.
<b>Engineering Controls</b>	Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended.
<b>PPE</b>	Wear splash-proof goggles, nitrile or viton (R) gloves, coveralls and a Type A (Organic vapour) respirator. If sanding dry product, wear: a Class P1 (Particulate) respirator. If spraying, with prolonged use, or if in confined areas, wear: impervious coveralls and an Air-line respirator.



### 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	CLEAR LIQUID	<b>Solubility (water)</b>	SOLUBLE
<b>Odour</b>	AMINE LIKE	<b>Specific Gravity</b>	0.95-1.05
<b>pH</b>	6.5-7.5	<b>% Volatiles</b>	<2%
<b>Vapour Pressure</b>	NOT AVAILABLE	<b>Flammability</b>	NON COMBUSTIBLE
<b>Vapour Density</b>	NOT AVAILABLE	<b>Flash Point</b>	NOT AVAILABLE
<b>Boiling Point</b>	100°C	<b>Upper Explosion Limit</b>	NOT AVAILABLE
<b>Melting Point</b>	NOT AVAILABLE	<b>Lower Explosion Limit</b>	NOT AVAILABLE
<b>Evaporation Rate</b>	NOT AVAILABLE		
<b>Autoignition Rate</b>	NOT AVAILABLE	<b>Decomposition Temperature</b>	NOT AVAILABLE
<b>Partition Coefficient</b>	NOT AVAILABLE	<b>Viscosity</b>	NOT AVAILABLE

### 10. STABILITY AND REACTIVITY

<b>Chemical Stability</b>	Stable under recommended conditions of storage.
<b>Conditions to avoid</b>	Avoid heat, sparks, open flames and other ignition sources.
<b>Material to avoid</b>	Incompatible with oxidising agents (eg. hypochlorites), acids (eg. nitric acid), alkalis (eg. hydroxides), heat and ignition sources.

**Product Name: EPIMAX 999UVX GLOSS ACTIVATOR**

**Hazardous Decomposition Products** May evolve toxic gases (carbon oxides, phenols, hydrocarbons) when heated to decomposition.  
**Hazardous Reactions** Hazardous polymerization is not expected to occur.

**11. TOXICOLOGICAL INFORMATION**

**Health hazard summary** Irritant - low to moderate toxicity. This product has the potential to cause adverse health effects with over exposure. Use safe work practices to avoid eye or skin contact and inhalation. May cause sensitisation by skin contact. The cured product is considered nontoxic.

**Eye** Irritant. Contact may result in irritation, lacrimation, pain and redness.

**Inhalation** Irritant. Over exposure whilst curing may result in irritation of the nose and throat, coughing, possible sensitisation with asthma-like symptoms and pulmonary oedema at high levels.

**Skin** Irritant. Contact may result in irritation, redness, rash and dermatitis. May cause sensitisation by skin contact.

**Ingestion** Low to moderate toxicity. Ingestion may result in gastrointestinal irritation, nausea, vomiting, abdominal pain and diarrhoea.

**Toxicity Data** **Short Term Hazards (Acute Exposure):**  
**LD50 values that is relevant for classification:**  
**CAS 112-24-3 Triethylenetriamine**  
Oral LD50 > 2780 mg/kg (rat)  
Dermal LD50 > 980 mg/kg (rabbit)  
**CAS 1477-55-0 m-Phenylenebis (methylamine)**  
Oral LD50 > 2780 mg/kg (rat)  
Dermal LD50 > 2000 mg/kg (rabbit)

**12. ECOLOGICAL INFORMATION**

**Other adverse effects** Limited ecotoxicity data was available for this product at the time this report was prepared. Ensure appropriate measures are taken to prevent this product from entering the environment.

**13. DISPOSAL CONSIDERATIONS**

**Waste disposal** Mix parts A + B together (small amounts), absorb with sand, vermiculite or similar and dispose of to an approved landfill site. Ensure protective equipment is worn when mixing. Do not seal containers/tins until reaction is complete. Contact the manufacturer for additional information. Prevent contamination of drains or waterways as environmental damage may result.

**Legislation** Dispose of in accordance with relevant local legislation.

**14. TRANSPORT INFORMATION**

**NOT CLASSIFIED AS A DANGEROUS GOOD THE CRITERIA OF THE ADG CODE**

<b>Shipping Name</b>	NONE ALLOCATED				
<b>UN No.</b>	NONE ALLOCATED	<b>DG CLASS</b>	NONE ALLOCATED	<b>Subsidiary Risk(s)</b>	NONE ALLOCATED

Product Name:

## EPIMAX 999UVX GLOSS ACTIVATOR

<b>Packing Group</b>	NONE ALLOCATED	<b>Hazchem Code</b>	NONE ALLOCATED	<b>GTEPG</b>	NONE ALLOCATED
----------------------	----------------	---------------------	----------------	--------------	----------------

### 15. REGULATORY INFORMATION

<b>Poison Schedule</b>	A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).
<b>AICS</b>	All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

### 16. OTHER INFORMATION

**Additional information** This product is used in conjunction with Epimax 999UVX GLOSS ACTIVATOR.

**WELDING - SANDING - CUTTING DRIED OR CURED PRODUCT:** If sanding, cutting or welding dried or cured product, adverse health effects may be avoided by the use of appropriate engineering controls and/or personal protective equipment. If welding, wear a Class P2 (Metal fume) respirator and depending on the nature of the surface being welded, additional protection (eg. for organic vapours/acid gas) may also be required. A Class P1 (Particulate) respirator is recommended if dust is generated.

**EPOXY - PHENOXY RESINS AND POLYURETHANES:** Where spray painting with two or more component epoxy resins or polyurethane paints is undertaken, an employee shall wear a air-line respirator, full length chemically resistant coveralls and gloves. Further, if an individual is to enter an enclosed booth where a vapour or gas curing process is occurring, an air-line respirator is required. Once cured, these resins are considered nontoxic.

**RESPIRATORS:** In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

**ABBREVIATIONS:**

ACGIH - American Conference of Industrial Hygienists.

ADG - Australian Dangerous Goods.

BEI - Biological Exposure Indice(s).

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.

CNS - Central Nervous System.

EC No - European Community Number.

HSNO - Hazardous Substances and New Organisms.

IARC - International Agency for Research on Cancer.

mg/m<sup>3</sup> - Milligrams per Cubic Metre.

NOS - Not Otherwise Specified.

pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).

ppm - Parts Per Million.

RTECS - Registry of Toxic Effects of Chemical Substances.

STEL - Short Term Exposure Limit.

SWA - Safe Work Australia.

TWA - Time Weighted Average.

Product Name:

**EPIMAX 999UVX GLOSS ACTIVATOR**