



EpiMax SAFETY DATA SHEET

Product Name **EpiMax 2175**

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name	EPIMAX TECHNOLOGIES PTY LTD
Address	4/3 Moorebank Avenue, Moorebank, NSW, AUSTRALIA, 2170
Telephone	1300 721 522
Fax	(02) 9904 3207
Emergency	1300 721 522
Synonym(s)	2175 • 7342175 – PRODUCT CODE • MIXED ALKALI SILCATE SOLUTION
Use(s)	CONCRETE DENSIFER
SDS Date	28/11/17

2. HAZARDS IDENTIFICATION

GHS Classifications Eye Damage / Irritation: Category 2A
Skin Corrosion / Irritation: Category 2

SIGNAL WORD **WARNING**



HAZARD STATEMENTS

H315 Causes skin irritation
H319 Causes serious eye irritation

RESPONSE STATEMENTS

P264 Wash skin thoroughly after handling
P280 Wear protective gloves, protective clothing and eye or face protection
P302+P352 IF ON SKIN: Wash with plenty of soap and water
P305+P351+P338 IF IN EYES: rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue Rinsing
P332+P313 If skin Irritation occurs, get medical advice/ attention
P337+P313 If eye irritation persists, get medical advice/ attention
P362 Take off contaminated clothing and wash before reuse

STORAGE STATEMENTS

P410 Protect from sunlight

Product Name: EpiMax 2175

P411 Store at temperatures not exceeding 30°C
P402+P404 Store in a dry place. Store in a closed container

DISPOSAL STATEMENTS

P501 IF they cannot be recycled, dispose of contents to an approved waste disposal plant and containers to landfill.

UN No.	NOT AVAILABLE	DG CLASS	NOT AVAILABLE	Subsidiary Risk(s)	None Allocated
Packing Group	NOT AVAILABLE	Hazchem Code	NOT AVAILABLE		

3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	Formula	CAS NO.	Content
SODIUM SILICATE	NOT AVAILABLE	1344-09-8	10%-30%
POTASSIUM SILICATE	NOT AVAILABLE	7732-18-5	<5%
LITHIUM SILICATE	NOT AVAILABLE	12627-14-4	<5%
WATER	H ₂ O		TO 100%

4. FIRST AID MEASURES

Eye	If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.
Inhalation	If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or an Airline respirator (in poorly ventilated areas). Apply artificial respiration if not breathing.
Skin	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.
Ingestion	For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.
Special Treatment	Treat symptomatically.

5. FIRE FIGHTING MEASURES

Special Hazards	Flammable. May evolve toxic gases (carbon oxides, phenols, hydrocarbons) when heated to decomposition. Eliminate all ignition sources including cigarettes, open flames, spark producing switches/tools, heaters, naked lights, pilot lights, mobile phones etc. when handling. Earth containers when dispensing fluids.
Advice for firefighters	Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.
Extinguishing Media	Dry agent, carbon dioxide or water fog. Prevent contamination of drains or waterways
Hazchem Code	3[Y]

Product Name: **EpiMax 2175**

6. ACCIDENTAL RELEASE MEASURES

Spillage Contact emergency services where appropriate. Use personal protective equipment. Clear area of all unprotected personnel. Ventilate area where possible. Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal. Eliminate all ignition sources.

7. STORAGE AND HANDLING

Storage Store tightly sealed in a cool, dry, well ventilated area, removed from oxidising agents, acids, alkalis, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Large storage areas should be bunded and have appropriate fire protection and ventilation systems. Vapours are highly flammable.

Precautions for safe handling Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

8. EXPOSURE CONTROLS / PERSONAL PROTECTIONS

Biological Limits No biological limit allocated.

Engineering Controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended.

PPE Wear splash-proof goggles, nitrile or viton (R) gloves, coveralls. A respirator is not usually needed. If spraying, with prolonged use, or if in confined areas, wear: impervious coveralls and an Air-line respirator.



9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	HAZY HOMOGENOUS LIQUID	Solubility (water)	INSOLUBLE
Odour	CHARACTERISTIC ODOUR	Specific Gravity	1.10-1.16
pH	NOT AVAILABLE	% Volatiles	NOT AVAILABLE
Vapour Pressure	NOT AVAILABLE	Flammability	NOT AVAILABLE
Vapour Density	NOT AVAILABLE	Flash Point	NOT AVAILABLE
Boiling Point	100°C	Upper Explosion Limit	NOT AVAILABLE
Melting Point	NOT AVAILABLE	Lower Explosion Limit	NOT AVAILABLE
Evaporation Rate	NOT AVAILABLE		
Autoignition Rate	NOT DETERMINED	Decomposition Temperature	NOT AVAILABLE
Partition Coefficient	NOT AVAILABLE	Viscosity	NOT AVAILABLE

Product Name: **EpiMax 2175**

10. STABILITY AND REACTIVITY

Chemical Stability	Stable under recommended conditions of storage.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources.
Material to avoid	Incompatible with oxidising agents (eg. hypochlorites), acids (eg. nitric acid), alkalis (eg. hydroxides), heat and ignition sources.
Hazardous Decomposition Products	May evolve toxic gases (carbon oxides, phenols, hydrocarbons) when heated to decomposition.
Hazardous Reactions	Hazardous polymerization is not expected to occur.

11. TOXICOLOGICAL INFORMATION

Health hazard summary	This product has the potential to cause adverse health effects with over exposure. Use safe work practices to avoid eye or skin contact and inhalation. May cause sensitisation by skin contact. The cured product is considered non toxic.
Eye	Irritant. Contact may result in irritation, lacrimation, pain, redness and conjunctivitis. May result in burns with prolonged contact.
Inhalation	Over exposure may result in irritation of the nose and throat, with coughing. Due to low vapour pressures, it is not thought to be an inhalation hazard.
Skin	Irritant . Contact may result in irritation, redness, rash and dermatitis. Can cause burns. May cause sensitisation by skin contact.
Ingestion	Irritant. Moderate toxicity. Ingestion may result in nausea, vomiting, abdominal pain, diarrhoea, fatigue, dizziness and unconsciousness.
Toxicity Data	There is no toxicological information available for this product.

12. ECOLOGICAL INFORMATION

Other adverse effects	Limited ecotoxicity data was available for this product at the time this report was prepared. Ensure appropriate measures are taken to prevent this product from entering the environment.
------------------------------	--

13. DISPOSAL CONSIDERATIONS

Waste disposal	Absorb with sand, vermiculite or similar and dispose of to an approved landfill site. Ensure protective equipment is worn when mixing. Do not seal containers/tins until reaction is complete. Contact the manufacturer for additional information. Prevent contamination of drains or waterways as environmental damage may result.
Legislation	Dispose of in accordance with relevant local legislation.

Product Name: **EpiMax 2175**

14. TRANSPORT INFORMATION

NOT CLASSIFIED AS A DANGEROUS GOOD THE CRITERIA OF THE ADG CODE

Shipping Name	NONE ALLOCATED				
UN No.	NONE ALLOCATED	UN No.	NONE ALLOCATED	UN No.	NONE ALLOCATED
Packing Group	NONE ALLOCATED	Packing Group	NONE ALLOCATED	Packing Group	

15. REGULATORY INFORMATION

Poison Schedule Classified as a Schedule 5 (S5) Poison using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).

AICS All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Additional information WELDING - SANDING - CUTTING DRIED OR CURED PRODUCT: If sanding, cutting or welding dried or cured product, adverse health effects may be avoided by the use of appropriate engineering controls and/or personal protective equipment. If welding, wear a Class P2 (Metal fume) respirator and depending on the nature of the surface being welded, additional protection (eg. for organic vapours/acid gas) may also be required. A Class P1 (Particulate) respirator is recommended if dust is generated.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

ABBREVIATIONS:

ACGIH - American Conference of Industrial Hygienists.

ADG - Australian Dangerous Goods.

BEI - Biological Exposure Indice(s).

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.

CNS - Central Nervous System.

EC No - European Community Number.

HSNO - Hazardous Substances and New Organisms.

IARC - International Agency for Research on Cancer.

mg/m³ - Milligrams per Cubic Metre.

NOS - Not Otherwise Specified.

pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).

PPM - Parts Per Million.

RTECS - Registry of Toxic Effects of Chemical Substances.

STEL - Short Term Exposure Limit.

SWA - Safe Work Australia.

TWA - Time Weighted Average.

Product Name: EpiMax 2175