



EpiMax 3500

Liquid Grout for Polished Concrete

Description

EpiMax 3500 Liquid Grout for Polished Concrete is a specially formulated grout and bonding agent. It is a single component product that reacts quickly with ground concrete dust to re-surface pinholes and divots created and exposed during the grinding process.

Advantages

- Single pack
- Low viscosity
- Good adhesion
- Aids cleaning/maintenance
- Low VOC
- Compatible with EpiMax densifier and sealer range

Typical properties

- Flashpoint - none
- pH - 7 - 9
- Colour, inherent - Clear when hard
- Odour - None
- Light foot traffic - overnight

Application

EpiMax 3500 is generally used before the 120-grit diamond stage.

Using a pump sprayer lightly wet the area with water. Do not saturate the concrete or leave puddles.

While the substrate is still damp, spray the EpiMax 3500 liberally (approximately 10m² per litre) 4m - 5m in front of the grinder.

Brush the floor with a broom to combine the EpiMax3500 with the concrete dust generated by the grinder, at the same time cleaning out the dust that is sitting in the pores of the concrete.

Using 120 grit diamonds, grind through the wet EpiMax 3500. The EpiMax 3500 will combine with the dust being from the grinder and a slurry will be created, that slurry will forced into holes.

Apply a suitable EpiMax densifier to the floor with a pump sprayer and mop around evenly with a micro-fiber mop

Allow the densifier to sit for 6 - 8 hours.

Packaging

EpiMax 3500 is available in 20 L packs.



EpiMax

EpiMax Systems Pty Limited

Sydney • Melbourne • Brisbane • Townsville • Canberra • Perth
Australia ☎ 1300 721 522 info@epimax.com.au

© Copyright 2020, All rights reserved