



EpiMax SAFETY DATA SHEET

Product Name **EpiMax 575 CG COMPOUND/ PART A**

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name	EPIMAX TECHNOLOGIES PTY LTD
Address	4/3 Moorebank Avenue, Moorebank, NSW, AUSTRALIA, 2170
Telephone	1300 721 522
Fax	(02) 9904 3207
Emergency	1300 721 522
Synonym(s)	575CG COMPOUND PART A • 4057520 – PRODUCT CODE • EPOXIDE RESIN
Use(s)	Two component epoxy system. Compound for epoxy resin system.
SDS Date	02/10/20

2. HAZARDS IDENTIFICATION

GHS Classification

Skin Corrosion / Irritation Category: 2
Eye Irritation Category: 2A
Skin Sensitization Category: 1
Acute Aquatic Hazard Category: 2
Chronic Aquatic Hazard Category: 2



HAZARD STATEMENTS

H315	Causes skin irritation
H319	Causes serious eye irritation
H317	May cause an allergic skin reaction
H411	Toxic to Aquatic life with long lasting effects

PREVENTION STATEMENTS

P280	Wear protective gloves/ protective clothing / eye protection / face protection
------	--------------------------------------------------------------------------------

Product Name: EpiMax 575CG PART A/ COMPOUND

P264 Wash hands, forearms and face thoroughly after handling
 P273 Avoid release to the environment
 P272 Contaminated work clothing should not be allowed out of the workplace

RESPONSE STATEMENTS

P362 Take off contaminated clothing and wash before reuse
 P302+352 IF ON SKIN: wash with plenty of soap and water.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses
 P333+P313 If skin irritation or rash occurs: Get medical advice / attention

DISPOSAL STATEMENTS

P501 Dispose of contents / container in accordance with local regulations

UN No.	3082	DG CLASS	9	Subsidiary Risk(s)	NONE ALLOCATED
Packing Group	III	Hazchem Code	NONE ALLOCATED		

3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	Formula	CAS NO.	Content
BISPHENOL-A-(EPICHLORHYDRIN); EPOXY RESIN	NOT AVAILABLE	25068-38-6	>30 - <60%
OXIRANE, MONO[(C12-14-ALKYLOXY)METHYL]	NOT AVAILABLE	68609-97-2	<10%
FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1CHLORO-2,3-EPOXYPROPANE AND PHENOL	NOT AVAILABLE	9003-36-5	<10%
OTHER NON SCHEDULED TO			100%

4. FIRST AID MEASURES

Eye If this product comes in contact with the eyes:

- Wash out immediately with fresh running water
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids
- Seek medical attention without delay; if pain persists or recurs seek medical attention
- Removal of contact lenses after and eye injury should only be undertaken by skilled personal

Inhalation If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or an Airline respirator (in poorly ventilated areas). Apply artificial respiration if not breathing.

Skin If skin contact occurs:

- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.
- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prosthesis such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor.

Product Name:

EpiMax 575CG PART A/ COMPOUND

Ingestion

If swallowed do NOT induce vomiting.

- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Seek medical advice..

Special Treatment

Treat symptomatically.

5. FIRE FIGHTING MEASURES

Special Hazards

May evolve toxic gases (carbon oxides, phenols, hydrocarbons) when heated to decomposition. Eliminate all ignition sources including cigarettes, open flames, spark producing switches/tools, heaters, naked lights, pilot lights, mobile phones etc. when handling. Earth containers when dispensing fluids.

Advice for firefighters

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

Extinguishing Media

Dry agent, carbon dioxide or water fog. Prevent contamination of drains or waterways

Hazchem Code

Not allocated

6. ACCIDENTAL RELEASE MEASURES

Spillage

Contact emergency services where appropriate. Use personal protective equipment. Clear area of all unprotected personnel. Ventilate area where possible. Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal. Eliminate all ignition sources.

7. STORAGE AND HANDLING

Storage

Store tightly sealed in a cool, dry, well ventilated area, removed from oxidising agents, acids, alkalis, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Large storage areas should be banded and have appropriate fire protection and ventilation systems.

Precautions for safe handling

DO NOT ALLOW CLOTHING WET WITH MATERIAL TO STAY IN CONTACT WITH SKIN. Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

Product Name:

EpiMax 575CG PART A/ COMPOUND

8. EXPOSURE CONTROLS / PERSONAL PROTECTIONS

Exposure Stds	Ingredient	Reference	TWA	STEL	
	BISPHENOL A	SWA (AUS)	--	0.02 mg/m ³	--

Biological Limits No biological limit allocated.

Engineering Controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof extraction ventilation is recommended. Flammable/explosive vapours may accumulate in poorly ventilated areas. Vapours are heavier than air and may travel some distance to an ignition source and flash back. Maintain vapour levels below the recommended exposure standard.

PPE Wear splash-proof goggles, nitrile or viton (R) gloves, coveralls and a Type A (Organic vapour) respirator. If sanding dry product, wear: a Class P1 (Particulate) respirator. If spraying, with prolonged use, or if in confined areas, wear: impervious coveralls and an Air-line respirator.



9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	LIQUID GEL STATE	Solubility (water)	INSOLUBLE
Odour	MILD ODOUR	Specific Gravity	1.2 - 1.4
pH	NOT AVAILABLE	% Volatiles	
Vapour Pressure	NOT AVAILABLE	Flammability	NOT FLAMMABLE
Vapour Density	NOT AVAILABLE	Flash Point	NOT AVAILABLE
Boiling Point	NOT DETERMINED	Upper Explosion Limit	NOT AVAILABLE
Melting Point	NOT DETERMINED	Lower Explosion Limit	NOT AVAILABLE
Evaporation Rate	NOT AVAILABLE		
Autoignition Rate	NOT AVAILABLE	Decomposition Temperature	NOT AVAILABLE
Partition Coefficient	NOT AVAILABLE	Viscosity	NOT AVAILABLE

10. STABILITY AND REACTIVITY

Chemical Stability	Stable under recommended conditions of storage.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources.
Material to avoid	Incompatible with oxidising agents (eg. hypochlorites), acids (eg. nitric acid), alkalis (eg. hydroxides), heat and ignition sources.
Hazardous Decomposition Products	May evolve toxic gases (carbon oxides, phenols, hydrocarbons) when heated to decomposition.
Hazardous Reactions	Hazardous polymerization is not expected to occur.

11. TOXICOLOGICAL INFORMATION

Product Name: EpiMax 575CG PART A/ COMPOUND

Health hazard summary Irritant - low to moderate toxicity. This product has the potential to cause adverse health effects with over exposure. Use safe work practices to avoid eye or skin contact and inhalation. May cause sensitisation by skin contact. The cured product is considered non toxic.

Eye Corrosive. Irritant. Contact may result in irritation, lacrimation, pain, redness and conjunctivitis. May result in burns with prolonged contact.

Inhalation Irritant. Over exposure may result in irritation of the nose and throat, with coughing. High level exposure may result in dizziness, drowsiness, breathing difficulties, pulmonary oedema and unconsciousness. May cause sensitisation by inhalation.

Skin Skin contact with the material may damage the health of the individual; systemic effects may result following absorption. This material can cause inflammation of the skin on contact in some persons. Epoxy materials may cause allergic and/or contact dermatitis responses, which may occur on exposure or may become apparent only after repeated exposures. Sensitisation is possible. Photoallergic dermatitis may result from contact with the material. This type of response can be elicited only in individuals who have been previously allergically sensitised to the chemical agent and appropriate radiation. The material may accentuate any pre-existing dermatitis condition.

Ingestion Moderate toxicity. Ingestion may result in nausea, vomiting, abdominal pain, diarrhoea, fatigue, dizziness and unconsciousness.

Toxicity Data There is no toxicological information available for this product.

12. ECOLOGICAL INFORMATION

Other adverse effects Limited ecotoxicity data was available for this product at the time this report was prepared. Ensure appropriate measures are taken to prevent this product from entering the environment.

13. DISPOSAL CONSIDERATIONS

Waste disposal Mix parts A + B together (small amounts), absorb with sand, vermiculite or similar and dispose of to an approved landfill site. Ensure protective equipment is worn when mixing. Do not seal containers/tins until reaction is complete. Contact the manufacturer for additional information. Prevent contamination of drains or waterways as environmental damage may result.

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD.



Product Name:

EpiMax 575CG PART A/ COMPOUND

Australian Dangerous Goods Code –ROAD AND RAIL

Shipping Name	ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID N.O.S				
UN No.	3082	DG CLASS	9	Subsidiary Risk(s)	None Allocated
Packing Group	III				

IATA Dangerous Goods Regulation - AIR

Shipping Name	ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID N.O.S				
UN No.	3082	DG CLASS	9	Subsidiary Risk(s)	None Allocated
Packing Group	III				

International Maritime Dangerous Goods Code- SEA

Shipping Name	ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID N.O.S				
UN No.	3082	DG CLASS	9	Subsidiary Risk(s)	None Allocated
Packing Group	III				

15. REGULATORY INFORMATION

Poison Schedule Classified as a Schedule 5 (S5) Poison using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).

AICS All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Additional information This product is used in conjunction with EpiMax 575 Hardener.

WELDING - SANDING - CUTTING DRIED OR CURED PRODUCT: If sanding, cutting or welding dried or cured product, adverse health effects may be avoided by the use of appropriate engineering controls and/or personal protective equipment. If welding, wear a Class P2 (Metal fume) respirator and depending on the nature of the surface being welded, additional protection (eg. for organic vapours/acid gas) may also be required. A Class P1(Particulate) respirator is recommended if dust is generated.

EPOXY - PHENOXY RESINS AND POLYURETHANES: Where spray painting with two or more component epoxy resins or polyurethane paints is undertaken, an employee shall wear a air-line respirator, full length chemically resistant coveralls and gloves. Further, if an individual is to enter an enclosed booth where a vapour or gas curing process is occurring, an air-line respirator is required. Once cured, these resins are considered non toxic.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken.

Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

ABBREVIATIONS:

ACGIH - American Conference of Industrial Hygienists.

Product Name:

EpiMax 575CG PART A/ COMPOUND

ADG - Australian Dangerous Goods.

BEI - Biological Exposure Indice(s).

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.

CNS - Central Nervous System.

EC No - European Community Number.

HSNO - Hazardous Substances and New Organisms.

IARC - International Agency for Research on Cancer.

mg/m³ - Milligrams per Cubic Metre.

NOS - Not Otherwise Specified.

pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).

PPM - Parts Per Million.

RTECS - Registry of Toxic Effects of Chemical Substances.

STEL - Short Term Exposure Limit.

SWA - Safe Work Australia.

TWA - Time Weighted Average



EpiMax SAFETY DATA SHEET

Product Name **EpiMax 575 CG HARDENER/ PART B**

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name	EPIMAX TECHNOLOGIES PTY LTD
Address	4/3 Moorebank Avenue, Moorebank, NSW, AUSTRALIA, 2170
Telephone	1300 721 522
Fax	(02) 9904 3207
Emergency	1300 721 522
Synonym(s)	575CG COMPOUND PART B • 4057520 – PRODUCT CODE • EPOXIDE RESIN
Use(s)	Two component epoxy system. Compound for epoxy resin system.
SDS Date	27/1/17

2. HAZARDS IDENTIFICATION

GHS Classification

Skin Corrosion / Irritation Category: 1b
Skin Sensitization Category: 1
Acute Toxicity (oral) Category: 4



HAZARD STATEMENTS

H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction

PREVENTION STATEMENTS

P260	Do not breathe mist, vapours
P264	Wash hands, forearms and face thoroughly after handling
P270	Do not eat, drink, or smoke when using this product
P272	Contaminated work clothing should not be allowed out of the workplace

Product Name: EpiMax 575CG PART B/ HARDENER

P280 Wear eye protection, protective clothing, protective gloves.

RESPONSE STATEMENTS

P362 Take off contaminated clothing and wash before reuse
 P302+352 IF ON SKIN: wash with plenty of soap and water.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses
 P333+P313 If skin irritation or rash occurs: Get medical advice / attention

DISPOSAL STATEMENTS

P501 Dispose of contents / container in accordance with local regulations

UN No.	2735	DG CLASS	8	Subsidiary Risk(s)	NONE ALLOCATED
Packing Group	III	Hazchem Code	NONE ALLOCATED		

3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	Formula	CAS NO.	Content
FATTY ACIDS, C18-UNSATD., DIMERS, OLIGOMERIC REACTION PRODUCTS WITH TALL-OIL FATTY ACIDS AND TRIETHYLENETETRAMINE	NOT AVAILABLE	68082-29-1	>30 - <60%
3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE	NOT AVAILABLE	2855-13-2	<10% - <30%
BENZYL ALCOHOL	NOT AVAILABLE	100-51-6	<10%
OTHER NON SCHEDULED TO			100%

4. FIRST AID MEASURES

Eye If this product comes in contact with the eyes:

- Wash out immediately with fresh running water
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids
- Seek medical attention without delay; if pain persists or recurs seek medical attention
- Removal of contact lenses after and eye injury should only be undertaken by skilled personal

Inhalation If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or an Airline respirator (in poorly ventilated areas). Apply artificial respiration if not breathing.

Skin If skin contact occurs:

- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.
- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prosthesis such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor.

Ingestion If swallowed do NOT induce vomiting.

Product Name:

EpiMax 575CG PART B/ HARDENER

- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Seek medical advice..

Special Treatment Treat symptomatically.

5. FIRE FIGHTING MEASURES

Special Hazards May evolve toxic gases (carbon oxides, phenols, hydrocarbons) when heated to decomposition. Eliminate all ignition sources including cigarettes, open flames, spark producing switches/tools, heaters, naked lights, pilot lights, mobile phones etc. when handling. Earth containers when dispensing fluids.

Advice for firefighters Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

Extinguishing Media Dry agent, carbon dioxide or water fog. Prevent contamination of drains or waterways

Hazchem Code Not allocated

6. ACCIDENTAL RELEASE MEASURES

Spillage Contact emergency services where appropriate. Use personal protective equipment. Clear area of all unprotected personnel. Ventilate area where possible. Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal. Eliminate all ignition sources.

7. STORAGE AND HANDLING

Storage Store tightly sealed in a cool, dry, well ventilated area, removed from oxidising agents, acids, alkalis, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Large storage areas should be bunded and have appropriate fire protection and ventilation systems.

Precautions for safe handling DO NOT ALLOW CLOTHING WET WITH MATERIAL TO STAY IN CONTACT WITH SKIN. Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

Product Name:

EpiMax 575CG PART B/ HARDENER

8. EXPOSURE CONTROLS / PERSONAL PROTECTIONS

Exposure Stds	Ingredient	Reference	TWA	STEL	
	BISPHENOL A	SWA (AUS)	--	0.02 mg/m ³	--

Biological Limits No biological limit allocated.

Engineering Controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof extraction ventilation is recommended. Flammable/explosive vapours may accumulate in poorly ventilated areas. Vapours are heavier than air and may travel some distance to an ignition source and flash back. Maintain vapour levels below the recommended exposure standard.

PPE Wear splash-proof goggles, nitrile or viton (R) gloves, coveralls and a Type A (Organic vapour) respirator. If sanding dry product, wear: a Class P1 (Particulate) respirator. If spraying, with prolonged use, or if in confined areas, wear: impervious coveralls and an Air-line respirator.



9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	BLACK LIQUID	Solubility (water)	INSOLUBLE
Odour	AMINE LIKE	Specific Gravity	1.05
pH	NOT AVAILABLE	% Volatiles	
Vapour Pressure	NOT AVAILABLE	Flammability	NOT FLAMMABLE
Vapour Density	NOT AVAILABLE	Flash Point	NOT AVAILABLE
Boiling Point	NOT DETERMINED	Upper Explosion Limit	NOT AVAILABLE
Melting Point	NOT DETERMINED	Lower Explosion Limit	NOT AVAILABLE
Evaporation Rate	NOT AVAILABLE		
Autoignition Rate	NOT AVAILABLE	Decomposition Temperature	NOT AVAILABLE
Partition Coefficient	NOT AVAILABLE	Viscosity	NOT AVAILABLE

10. STABILITY AND REACTIVITY

Chemical Stability	Stable under recommended conditions of storage.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources.
Material to avoid	Incompatible with oxidising agents (eg. hypochlorites), acids (eg. nitric acid), alkalis (eg. hydroxides), heat and ignition sources.
Hazardous Decomposition Products	May evolve toxic gases (carbon oxides, phenols, hydrocarbons) when heated to decomposition.
Hazardous Reactions	Hazardous polymerization is not expected to occur.

11. TOXICOLOGICAL INFORMATION

Health hazard summary	Irritant - low to moderate toxicity. This product has the potential to cause adverse health effects with over exposure. Use safe work practices to avoid eye or skin contact and inhalation. May cause sensitisation by skin contact. The cured product is considered non toxic.
Eye	Corrosive. Irritant. Contact may result in irritation, lacrimation, pain, redness and conjunctivitis. May result in burns with prolonged contact.
Inhalation	Irritant. Over exposure may result in irritation of the nose and throat, with coughing. High level exposure may result in dizziness, drowsiness, breathing difficulties, pulmonary oedema and unconsciousness. May cause sensitisation by inhalation.
Skin	Skin contact with the material may damage the health of the individual; systemic effects may result following absorption. This material can cause inflammation of the skin on contact in some persons. Epoxy materials may cause allergic and/or contact dermatitis responses, which may occur on exposure or may become apparent only after repeated exposures. Sensitisation is possible. Photoallergic dermatitis may result from contact with the material. This type of response can be elicited only in individuals who have been previously allergically sensitised to the chemical agent and appropriate radiation. The material may accentuate any pre-existing dermatitis condition.
Ingestion	Moderate toxicity. Ingestion may result in nausea, vomiting, abdominal pain, diarrhoea, fatigue, dizziness and unconsciousness.
Toxicity Data	There is no toxicological information available for this product.

12. ECOLOGICAL INFORMATION

Other adverse effects	Limited ecotoxicity data was available for this product at the time this report was prepared. Ensure appropriate measures are taken to prevent this product from entering the environment.
------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

13. DISPOSAL CONSIDERATIONS

Waste disposal	Mix parts A + B together (small amounts), absorb with sand, vermiculite or similar and dispose of to an approved landfill site. Ensure protective equipment is worn when mixing. Do not seal containers/tins until reaction is complete. Contact the manufacturer for additional information. Prevent contamination of drains or waterways as environmental damage may result.
Legislation	Dispose of in accordance with relevant local legislation.

Product Name:

EpiMax 575CG PART B/ HARDENER

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD.



Australian Dangerous Goods Code –ROAD AND RAIL

Shipping Name	POLYAMINES, LIQUID, CORROSIVE, N.O.S.				
UN No.	2735	DG CLASS	8	Subsidiary Risk(s)	None Allocated
Packing Group	III				

IATA Dangerous Goods Regulation - AIR

Shipping Name	POLYAMINES, LIQUID, CORROSIVE, N.O.S.				
UN No.	2735	DG CLASS	8	Subsidiary Risk(s)	None Allocated
Packing Group	III				

International Maritime Dangerous Goods Code- SEA

Shipping Name	POLYAMINES, LIQUID, CORROSIVE, N.O.S.				
UN No.	2735	DG CLASS	8	Subsidiary Risk(s)	None Allocated
Packing Group	III				

15. REGULATORY INFORMATION

Poison Schedule Classified as a Schedule 5 (S5) Poison using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).

AICS All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Additional information This product is used in conjunction with EpiMax 575CG Part A.

WELDING - SANDING - CUTTING DRIED OR CURED PRODUCT: If sanding, cutting or welding dried or cured product, adverse health effects may be avoided by the use of appropriate engineering controls and/or personal protective equipment. If welding, wear a Class P2 (Metal fume) respirator and depending on the nature of the surface being welded, additional protection (eg. for organic vapours/acid gas) may also be required. A Class P1(Particulate) respirator is recommended if dust is generated.

EPOXY - PHENOXY RESINS AND POLYURETHANES: Where spray painting with two or more component epoxy resins or polyurethane paints is undertaken, an employee shall wear a air-line respirator, full length chemically resistant coveralls and gloves. Further, if an individual is to enter an enclosed booth where a vapour or gas curing process is occurring, an air-line respirator is required. Once cured, these resins are considered non toxic.

Product Name:

EpiMax 575CG PART B/ HARDENER

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken.

Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

ABBREVIATIONS:

ACGIH - American Conference of Industrial Hygienists.

ADG - Australian Dangerous Goods.

BEI - Biological Exposure Indice(s).

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.

CNS - Central Nervous System.

EC No - European Community Number.

HSNO - Hazardous Substances and New Organisms.

IARC - International Agency for Research on Cancer.

mg/m³ - Milligrams per Cubic Metre.

NOS - Not Otherwise Specified.

pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).

PPM - Parts Per Million.

RTECS - Registry of Toxic Effects of Chemical Substances.

STEL - Short Term Exposure Limit.

SWA - Safe Work Australia.

TWA - Time Weighted Average